



professional tractor powered moving equipment

# **Striker**

An industry leader with over 30 years experience designing and manufacturing tractor mounted mowers, Trimax Mowing Systems now offers **Striker** as the ultimate companion for compact tractors.

Striker is a multi-spindled rotary mower with low maintenance costs that produces a clean finish with even grass distribution.

With full width rollers for an attractive striped pattern, Trimax Striker is a versatile mower that will turn grass spaces into attractive turf for years to come.





# compact versatility will fraction.

## Lazerbladez

Striker is fitted with Trimax LazerBladez™, a unique blade system with a carefully engineered centre of gravity and distinctive tilt-forward blade design. Utilising the LazerBladez™ full length cutting edge, Striker produces a clean finish even when mowing at high ground speeds.



Perfect for areas where larger tractors cannot easily operate.

# Advanced design

Striker is an all-new design incorporating decades of experience with multi-spindled rotary roller mowers. Lighter than other Trimax mowers, it retains the attention to detail that minimises downtime and makes servicing easy. The cutting system, body integrity and sealed ball bearing spindles have been proven with extensive and rigorous testing.

# Safety

Striker meets or exceeds international safety standards and is backed up by full operator's manuals and online support. Striker is a mower that can be used with confidence even when mowing in confined areas.

Easily accessible height adjusters makes changes fast and simple.

LazerBladez™ are made with high grade alloy steel providing a significant increase in blade and bolt life for added safety and lower operating costs.

### Low Maintenance

With a limited number of carefully positioned grease points and robust spindles with sealed ball bearings this mower has low maintenance requirements.

Striker meets stringent international safety standards (ISO 5395).





(A) Three-point linkage

Floating top link allows mower to follow ground contours. Linkage suits Category 1 tractors only.

(B) Gearbox

Heavy duty for long life. Inbuilt overrun clutch.

(c) Drive belt tensioning

Easy and quick to adjust.

(D) Transmission guards

Stainless steel for long life and good looks.

(E) Grease points

Roller bearings and driveshaft only.

(F) Cutting height

Infinitely variable to suit every requirement. Easily accessible height adjusters.

(G) Cutting system

Small diameter for more cuts per metre.

Trimax exclusive LazerBladez™ for high performance and long life.

(H) Full width rollers

(I) Body

Rollers front and rear to minimise scalping.

Large diameters roll more easily.

Inboard bearings with custom greasing for longer life.

Single rear roller option.

Model 150 Model 190 **Cutting Width** 1.46m (57.5") 1.94m (76.5") Overall Width 1.56m (61.5") 2.04m (80.5") Overall Length 1.16m (45.5") 1.16m (45.5") Cut Height Range 10 - 100mm (0.4 - 4") 10 - 100mm (0.4 - 4") No. of Spindles 3 4 Approx. Weight 310kg (680 lbs) 385kg (850 lbs) Minimum Power 15kW (20hp) 18.5kW (25hp) Maximum Power 33.5kW (45hp) 45kW (60hp)

(J) Blade spindles

Robust ball bearing design.

Labyrinth system prevents fibrous material wrapping into bearings.

Top cap protects top bearing seals.

Very simple maintenance.

(K) Underbody design

Large underbody volume to cope with heavy conditions. Individual cutting chambers spread clippings evenly.

(L) Safety

Meets stringent international safety standards.

Front and rear rollers and side channels contain thrown objects.



WARNING: Machinery shown in this publication may have protective quards removed for clarity. Trimax strongly recommends the use of safety guards and shields during operation to reduce the risk of property damage, serious bodily injury or even death from thrown objects or contact with moving parts. Read the operator's manual before use. insist on Trimax **Genuine Parts** 



www.trimaxmowers.com

#### **New Zealand**

70 Maleme Street PO Box 2150, Tauranga 3041 New Zealand

phone: +64 7 541 0411 (SALES/ADMIN) phone: +64 7 543 1897 (PARTS) . fax: +64 7 541 0412

email: sales@trimaxmowers.co.nz

#### **United Kingdom**

Unit 11B, Hill Farm Estate, Irthlingborough Road Little Addington, Kettering, Northamptonshire NN14 4AS, United Kingdom

phone: 01933 652235 (SALES/ADMIN) phone: 01933 652246 (PARTS) fax: 01933 652254

email: info@trimaxmowers.co.uk